

## PGP Series

A general purpose range of light duty pressed steel, zinc plated castors offering Top plate or Single bolt hole fitting options. Grey non-marking rubber tyred wheels make these suitable for use in most areas as they will not damage or mark flooring or carpets. Wheel brake options available in all sizes. Generous load capacities up to 100kg make these a good adaptable solution for lightweight mobile equipment.



### Top Plate fit Swivel

| Wheel Dia. (mm) | Tread Width (mm) | Overall Height (mm) | Load Cap. (kg) | Offset (mm) | Bearing Type | Fitting Dimensions |                     |                    | Part Number       |
|-----------------|------------------|---------------------|----------------|-------------|--------------|--------------------|---------------------|--------------------|-------------------|
|                 |                  |                     |                |             |              | Top Plate (mm)     | Fixing Centres (mm) | Fitting bolts (mm) |                   |
| 50              | 17               | 72                  | 50             | 23          | Plain        | 50 x 50            | 36 x 36             | 6                  | <b>MS50PGP12</b>  |
| 75              | 21               | 104                 | 70             | 30          | Plain        | 65 x 65            | 49 x 49             | 6                  | <b>MS75PGP12</b>  |
| 100             | 27               | 135                 | 80             | 38          | Plain        | 76 x 76            | 57 x 57             | 8                  | <b>MS100PGP12</b> |
| 125             | 27               | 159                 | 100            | 47          | Plain        | 76 x 76            | 57 x 57             | 8                  | <b>MS125PGP12</b> |



### Single Bolt hole fit Swivel

| Wheel Dia. (mm) | Tread Width (mm) | Overall Height (mm) | Load Cap. (kg) | Offset (mm) | Bearing Type | Fitting Dimensions |                    | Part Number      |
|-----------------|------------------|---------------------|----------------|-------------|--------------|--------------------|--------------------|------------------|
|                 |                  |                     |                |             |              | Bolt hole (mm)     | Fitting bolts (mm) |                  |
| 50              | 17               | 70                  | 50             | 23          | Plain        | 10                 | 10                 | <b>MS50PGP22</b> |
| 75              | 21               | 102                 | 70             | 30          | Plain        | 10                 | 10                 | <b>MS75PGP22</b> |
| 100             | 27               | 132                 | 80             | 38          | Plain        | 10                 | 10                 | <b>MS100PGP2</b> |
| 125             | 27               | 156                 | 100            | 47          | Plain        | 10                 | 10                 | <b>MS125PGP2</b> |



### Top Plate fit Braked

| Wheel Dia. (mm) | Tread Width (mm) | Overall Height (mm) | Load Cap. (kg) | Offset (mm) | Bearing Type | Fitting Dimensions |                     |                    | Part Number       |
|-----------------|------------------|---------------------|----------------|-------------|--------------|--------------------|---------------------|--------------------|-------------------|
|                 |                  |                     |                |             |              | Top Plate (mm)     | Fixing Centres (mm) | Fitting bolts (mm) |                   |
| 50              | 17               | 72                  | 50             | 23          | Plain        | 50 x 50            | 36 x 36             | 6                  | <b>MB50PGP12</b>  |
| 75              | 21               | 104                 | 70             | 30          | Plain        | 65 x 65            | 49 x 49             | 6                  | <b>MB75PGP12</b>  |
| 100             | 27               | 135                 | 80             | 38          | Plain        | 76 x 76            | 57 x 57             | 8                  | <b>MB100PGP12</b> |
| 125             | 27               | 159                 | 100            | 47          | Plain        | 76 x 76            | 57 x 57             | 8                  | <b>MB125PGP12</b> |



### Single Bolt hole fit Braked

| Wheel Dia. (mm) | Tread Width (mm) | Overall Height (mm) | Load Cap. (kg) | Offset (mm) | Bearing Type | Fitting Dimensions |                    | Part Number       |
|-----------------|------------------|---------------------|----------------|-------------|--------------|--------------------|--------------------|-------------------|
|                 |                  |                     |                |             |              | Bolt hole (mm)     | Fitting bolts (mm) |                   |
| 50              | 17               | 70                  | 50             | 23          | Plain        | 10                 | 10                 | <b>MB50PGP22</b>  |
| 75              | 21               | 102                 | 70             | 30          | Plain        | 10                 | 10                 | <b>MB75PGP22</b>  |
| 100             | 27               | 132                 | 80             | 38          | Plain        | 10                 | 10                 | <b>MB100PGP22</b> |
| 125             | 27               | 156                 | 100            | 47          | Plain        | 10                 | 10                 | <b>MB125PGP22</b> |